

No Sound Series

1700

XNS


Certified for:

- Sound insulation **54 dB**
- Fire resistance: **60 min.**
- Insulation from smoke **1,50 m³ / h / m - 25 Pa**
- Usage cycles **200.000 cycles**


Protects from:

- Air
- Water
- Light
- Insects

Not an obstacle for disabled persons




STANDARD ACCESSORIES



Standard measurements (mm)	430	530	630	730	830	930	1030	1130	1230	1330	1430	1530	1630	1730	1830	Longer lengths on request
Max shortening (mm)	120	100	100	100	100	100	100	100	100	100	150	150	150	150	150	

FASTENING SYSTEMS



Remove and screw

Mechanism (PATENTED) with the parallel descent of the moving profile with gasket, characterised by the DUAL ADJUSTMENT (screw E: descent - screw R: incline) for a strong even pressure on the entire length.

STANDARD: Cardboard box with 32 pcs + 32 standard accessory packs.

MAIN APPLICATIONS



Wood door

Armoured door



Extruded profiles in aluminium alloy 6060 - high performance wrap-around silicone gasket - elements printed in self-lubricating nylon + nylon reinforced with 30% glass fibre - threaded rods in burnished iron - 7 mm hexagonal button and Ø 6 mm brass bushing - coil springs in treated stainless steel.

OPTIONAL ACCESSORIES

Details on page 102

1 Nylon plate

CA101 CA102 CA104

100 pcs pack
 brown, white

2 Insulating nylon plate with silicon gasket

PI001 PI002 PI002-R

20 pcs pack
 brown, white


3 Using brackets

SCN002A SCN002B-1712

20 pcs pack
 steel, brown

Application examples

Smooth frame



BUTTON (E): round nylon, square nylon, bevelled nylon, rolling nylon (pivot).

OPTIONAL: Cardboard box with 15 polyethylene bags with 1 pc + 1 standard accessory pack + assembly instructions.